

group.com/nsn/5306-00-147-6333

| NSN 5306-00-147-6 Machine Bolt - Page 1 of 2 |
|--------------------------------------------------------|
| View Online at https://aerobasegroup.com |
| Thread Class: |
| За |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.880 inches |
| Fastener Length: |
| 9.300 inches |
| Head Style: |
| Hexagon |
| Head Height: |
| 0.340 inches |
| Width Between Flats: |
| Between 0.550 inches and 0.564 inches |
| Hole Diameter: |
| 0.070 inches |
| Thread Diameter: |
| 0.375 inches |
| Grip Length: |
| 8.420 inches |
| Hole Quantity: |
| 6 |
| Hole Type: |
| Drilled |
| Features Provided: |
| Finished head |
| Thready Qty Per Inch (tpi): |
| 24 |
| Hardness Rating: |
| 26.0 rockwell c and 32.0 rockwell c |
| Hole Configuration Style: |
| Hexagon flats |
| Surface Finish: |
| 63.0 microinches grip |

63.0 microinches grip Material: Steel comp 8740 **Material Specification:** Ams 6322 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Ams 2400 assn standard single treatment response

NSN 5306-00-147-6333

Machine Bolt - Page 2 of 2

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

