

View Online at <https://aerobasegroup.com/nsn/5306-00-149-0751>

**Thread Direction:**

Right-hand

**Fastener Length:**

1.250 inches

**Head Style:**

Pan no. 2

**Head Diameter:**

Between 0.776 inches and 0.786 inches

**Head Height:**

0.312 inches

**Distance From Center Of Head To Center Of Shank:**

0.156 inches

**Shank Unthreaded Hole Diameter:**

0.141 inches first hole

**Internal Drive Style:**

W/o internal drive

**Thread Diameter:**

0.562 inches

**Nonstandard Thread Pitch Diameter:**

+0.5234/+0.5625 inches

**Thready Qty Per Inch (tpi):**

18

**Min. Tensile Strength (psi):**

135000 pounds per square inch

**Hardness Rating:**

269.0 brinell standard and 307.0 brinell standard

**Minimum Yield Strength:**

11000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.094 inches first hole

**Material:**

Steel comp 3140 or steel comp 4140

**Material Specification:**

Sae assn standard all material responses

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0