

View Online at <https://aerobasegroup.com/nsn/5306-00-149-9775>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.650 inches and 0.730 inches

**Fastener Length:**

1.300 inches

**Head Style:**

Hexagon

**Head Height:**

0.260 inches

**Width Between Flats:**

Between 0.741 inches and 0.750 inches

**Shank Unthreaded Hole Diameter:**

0.094 inches all holes and 0.101 inches all holes

**First Diameter From Head:**

Between 0.494 inches and 0.500 inches

**Second Diameter From Head:**

Between 0.434 inches and 0.438 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.120 inches and 0.180 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

Between 0.500 inches and 0.540 inches

**Thread Diameter:**

0.500 inches

**Thready Qty Per Inch (tpi):**

20

**Hardness Rating:**

32.0 rockwell c and 36.0 rockwell c

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.160 inches all holes

**Externally Relieved Body Diameter Quantity:**

2

**Special Features:**

Two holes in shank at 90 deg. To each other

**Material:**

Steel comp 8735 or steel comp 4140

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Ams 2400 assn standard single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0