

View Online at <https://aerobasegroup.com/nsn/5306-00-149-9922>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.913 inches and 0.963 inches

**Fastener Length:**

Between 3.610 inches and 3.640 inches

**Head Style:**

Bevel-conical

**Head Diameter:**

Between 0.988 inches and 1.000 inches

**Head Height:**

0.595 inches

**Hole Diameter:**

0.070 inches

**Shank Unthreaded Hole Diameter:**

0.141 inches first hole and 0.146 inches first hole

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.625 inches

**Width Across Flats:**

Between 0.563 inches and 0.566 inches

**Hole Quantity:**

1

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

18

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hole Configuration Style:**

Hexagon flats

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

3.428 inches first hole and 3.448 inches first hole

**Material:**

Steel comp e4340 or steel comp 8740 or steel comp 6150 or steel comp 3140 or steel comp 3135

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification all treatment responses

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas150 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0