
# NSN 5306-00-150-3492

Machine Bolt - Page 1 of 2



# Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

## Thread Length:

Between 0.630 inches and 0.690 inches

# Fastener Length:

1.562 inches

#### **Head Style:**

Double hexagon w/hole

#### **Head Height:**

0.260 inches

#### Width Between Flats:

0.250 inches

#### Extended Washer Diameter:

0.375 inches

#### **Extended Washer Thickness:**

0.040 inches

#### **Thread Diameter:**

0.190 inches

# Grip Length:

Between 0.872 inches and 0.932 inches

# **Features Provided:**

Finished head

#### Thready Qty Per Inch (tpi):

32

#### Min. Tensile Strength (psi):

130000 pounds per square inch

#### Hardness Rating:

248.0 brinell standard and 341.0 brinell standard

#### Minimum Yield Strength:

85000 pounds per square inch

#### Surface Finish:

32.0 microinches threads

#### Material:

Iron alloy 660

#### **Material Specification:**

Ams 5731 assn standard single material response

# Thread Series Designator:

Unjf

#### Shelf Life:

N/a



# NSN 5306-00-150-3492

Machine Bolt - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

