## NSN 5306-00-150-3553

Shear Bolt - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5306-00-150-3553  |
|--|
| Thread Class:  |
| 3a   |
| Thread Direction:  |
| Right-hand   |
| Thread Length:   |
| Between 0.564 inches and 0.631 inches  |
| Fastener Length:   |
| Between 2.262 inches and 2.309 inches  |
| Head Style:  |
| Double hexagon   |
| Head Height:   |
| Between 0.318 inches and 0.338 inches  |
| Width Between Flats:   |
| Between 0.865 inches and 0.877 inches  |
| Grip Diameter:   |
| Between 0.5607 inches and 0.5616 inches  |
| Thread Diameter:   |
| 0.562 inches   |
| Grip Length:   |
| Between 1.688 inches and 1.698 inches  |
| Thready Qty Per Inch (tpi):  |
| 18   |
| Min. Tensile Strength (psi):   |
| 220000 pounds per square inch  |
| Hardness Rating:   |
| 46.0 rockwell c and 50.0 rockwell c  |
| Material:  |
| Steel comp h11 or steel  |
| Material Specification:  |
| Ams 6485 assn standard 1st material response or ams 6487 assn standard 1st material response or sps-m-107 fscm 56878 mfr ref 2nd |
| material response  |
| Surface Treatment:   |
| Cadmium  |
| Surface Treatment Specification:   |
| Nas 672 assn standard single treatment response  |
| Thread Series Designator:  |
| Unjf   |
| Specification Data:  |
| 26512-6b511b manufacturers standard  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |

--

## NSN 5306-00-150-3553

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0