
NSN 5306-00-150-3553

Shear Bolt - Page 1 of 2





Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.564 inches and 0.631 inches

Fastener Length:

Between 2.262 inches and 2.309 inches

Head Style:

Double hexagon

Head Height:

Between 0.318 inches and 0.338 inches

Width Between Flats:

Between 0.865 inches and 0.877 inches

Grip Diameter:

Between 0.5607 inches and 0.5616 inches

Thread Diameter:

0.562 inches

Grip Length:

Between 1.688 inches and 1.698 inches

Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

220000 pounds per square inch

Hardness Rating:

46.0 rockwell c and 50.0 rockwell c

Material:

Steel comp h11 or steel

Material Specification:

Ams 6485 assn standard 1st material response or ams 6487 assn standard 1st material response or sps-m-107 fscm 56878 mfr ref 2nd material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Nas 672 assn standard single treatment response

Thread Series Designator:

Unjf

Specification Data:

26512-6b511b manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

NSN 5306-00-150-3553

Shear Bolt - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

