

View Online at <https://aerobasegroup.com/nsn/5306-00-150-3556>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.843 inches and 0.893 inches

**Fastener Length:**

Between 2.603 inches and 2.633 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.610 inches and 0.628 inches

**Width Between Flats:**

Between 0.679 inches and 0.690 inches

**Extended Washer Diameter:**

Between 1.040 inches and 1.050 inches

**Extended Washer Thickness:**

Between 0.140 inches and 0.160 inches

**Grip Diameter:**

Between 0.6230 inches and 0.6240 inches

**End Application:**

A-10 thunderbolt, f-15 eagle, prowler ea-6b aircraft

**Thread Diameter:**

0.625 inches

**Grip Length:**

Between 1.740 inches and 1.760 inches

**Thready Qty Per Inch (tpi):**

18

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Hardness Rating:**

46.0 rockwell c and 50.0 rockwell c

**Material:**

Steel comp h11 or steel

**Material Specification:**

Ams 6485 assn standard 1st material response or ams 6487 assn standard 1st material response or sps-m-107 fscm 56878 mfr ref 2nd material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Nas 672 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

56878-lwb22 manufacturers standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0