NSN 5306-00-150-3562

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-150-3562

Thread Class:
3a
Thread Direction:
Right-hand Thread Longth:
Thread Length:
Between 0.535 inches and 0.585 inches
Fastener Length: Between 2.107 inches and 2.137 inches
Head Style: Double hoveren w/bele
Double hexagon w/hole
Head Height:
Between 0.378 inches and 0.398 inches
Width Between Flats:
Between 0.430 inches and 0.439 inches
Extended Washer Diameter:
Between 0.639 inches and 0.649 inches
Extended Washer Thickness:
Between 0.081 inches and 0.101 inches
Grip Diameter:
Between 0.3735 inches and 0.3745 inches
Thread Diameter:
0.375 inches
Grip Length:
Between 1.552 inches and 1.572 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
220000 pounds per square inch
Hardness Rating:
46.0 rockwell c and 50.0 rockwell c
Product Name:
Navy special project
Material:
Steel comp h11 or steel
Material Specification:
Ams 6485 assn standard 1st material response or ams 6487 assn standard 1st material response or sps-m-107 fscm 56878 mfr ref 2nd
material response
Surface Treatment:
Cadmium
Surface Treatment Specification:
Nas 672 assn standard single treatment response

Unjf

Thread Series Designator:

NSN 5306-00-150-3562

Shear Bolt - Page 2 of 2



Spec	ifi	cation	Data
------	-----	--------	------

26512-gb511w6 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0