

View Online at <https://aerobasegroup.com/nsn/5306-00-150-3562>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.535 inches and 0.585 inches

Fastener Length:

Between 2.107 inches and 2.137 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.378 inches and 0.398 inches

Width Between Flats:

Between 0.430 inches and 0.439 inches

Extended Washer Diameter:

Between 0.639 inches and 0.649 inches

Extended Washer Thickness:

Between 0.081 inches and 0.101 inches

Grip Diameter:

Between 0.3735 inches and 0.3745 inches

Thread Diameter:

0.375 inches

Grip Length:

Between 1.552 inches and 1.572 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

220000 pounds per square inch

Hardness Rating:

46.0 rockwell c and 50.0 rockwell c

Product Name:

Navy special project

Material:

Steel comp h11 or steel

Material Specification:

Ams 6485 assn standard 1st material response or ams 6487 assn standard 1st material response or sps-m-107 fscm 56878 mfr ref 2nd material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Nas 672 assn standard single treatment response

Thread Series Designator:

Unjf

Specification Data:

26512-gb511w6 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0