## NSN 5306-00-150-3578

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-150-3578

| Thread Class:                                       |
|---|
| 3a  |
| Thread Direction:                                   |
| Right-hand  |
| Thread Length:                                      |
| Between 0.440 inches and 0.507 inches               |
| Fastener Length:                                    |
| Between 1.325 inches and 1.372 inches               |
| Head Style:   |
| •   |
| Double hexagon                                      |
| Head Height:  Between 0.247 inches and 0.267 inches |
| Width Between Flats:                                |
|   |
| Between 0.678 inches and 0.689 inches               |
| Grip Diameter:                                      |
| Between 0.4358 inches and 0.4367 inches             |
| Thread Diameter:                                    |
| 0.438 inches  |
| Grip Length:  |
| Between 0.865 inches and 0.885 inches               |
| Thready Qty Per Inch (tpi):                         |
| 20  |
| Min. Tensile Strength (psi):                        |
| 220000 pounds per square inch                       |
| Hardness Rating:                                    |
| 46.0 rockwell c and 50.0 rockwell c                 |
| Material:   |
| Steel or steel comp h11                             |
| Material Specification:                             |
| Sps-m-107 fscm 56878 mfr ref 1st material response  |
| Surface Treatment:                                  |
| Cadmium   |
| Surface Treatment Specification:                    |
| Nas 672 assn standard single treatment response     |
| Thread Series Designator:                           |
| Unjf  |
| Specification Data:                                 |
| 26512-gb511b manufacturers standard                 |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:                                    |
|   |

--

## NSN 5306-00-150-3578

Shear Bolt - Page 2 of 2



| _  |     |         |     |     |    |  |
|----|-----|---------|-----|-----|----|--|
| 11 | em) | <br>tor | 172 | + 1 | nn |  |
|    |     |         |     |     |    |  |

No

Fiig:

A003b0