

View Online at <https://aerobasegroup.com/nsn/5306-00-150-3595>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 1.349 inches and 1.416 inches

Fastener Length:

Between 3.609 inches and 3.656 inches

Head Style:

Double hexagon

Head Height:

Between 0.680 inches and 0.700 inches

Width Between Flats:

Between 1.801 inches and 1.814 inches

Hole Diameter:

0.035 inches

Grip Diameter:

Between 1.2475 inches and 1.2490 inches

Shank Unthreaded Hole Diameter:

0.136 inches first hole and 0.146 inches first hole

Thread Diameter:

1.250 inches

Grip Length:

Between 2.240 inches and 2.260 inches

Hole Quantity:

1

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

12

Min. Tensile Strength (psi):

220000 pounds per square inch

Hardness Rating:

46.0 rockwell c and 50.0 rockwell c

Hole Configuration Style:

Hexagon flats

Distance From Head Largest Bearing Surface To Shank Hole Center:

3.439 inches first hole and 3.471 inches first hole

Material:

Steel or steel comp h11

Material Specification:

Sps-m-107 fscm 56878 mfr ref 1st material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, ty2, cl3 federal specification all treatment responses

Thread Series Designator:

Unjf

Specification Data:

26512-gb511b20d36 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0