## NSN 5306-00-150-4792

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-150-4792 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.704 inches and 0.724 inches **Fastener Length:** 0.812 inches **Head Style:** Hexagon **Head Height:** 0.296 inches Width Between Flats: Between 0.553 inches and 0.564 inches **Hole Diameter:** 0.070 inches **Shank Unthreaded Hole Diameter:** 0.070 inches first hole **Thread Diameter:** 0.375 inches **Grip Length:** Between 0.088 inches and 0.108 inches **Hole Quantity: Hole Type:** Drilled **Features Provided:** Finished head Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 130000 pounds per square inch **Hardness Rating:** 248.0 brinell standard and 341.0 brinell standard Minimum Yield Strength: 85000 pounds per square inch **Hole Configuration Style:** Hexagon longitudinal hole **Surface Finish:** 

32.0 microinches threads Material: Iron alloy 660

## NSN 5306-00-150-4792

Machine Bolt - Page 2 of 2



Material Specification:
-------------------------

Ams 5731 assn standard single material response

**Thread Series Designator:** 

Unjf

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

No

Fiig:

A003b0