## NSN 5306-00-150-9915



Clevis Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-00-150-9915 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.297 inches **Fastener Length:** 1.219 inches **Head Style: Button Head Diameter:** Between 0.359 inches and 0.391 inches **Head Height:** Between 0.078 inches and 0.110 inches **Groove Diameter:** 0.141 inches Single Shear Strength: 2125 pounds per square inch **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Material: Steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4140 or steel comp 4130 or steel comp 4037 **Material Specification:** Mil-s-6049 military specification 1st material response or mil-s-6050 military specification 2nd material response or mil-s-6098 military specification 3rd material response or mil-s-5626 military specification 4th material response or mil-s-6758 military specification 5th material response or mil-s-8695 military specification 6th material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2 cl 3 federal specification all treatment responses **Thread Series Designator:** Unf **Departure From Cited Document:** Thread t per mil-s-7742 except major diameter is not to exceed maximum allow bolt shank dia

**Demilitarization:** No

**Unit Of Measure:** 

Shelf Life:

N/a

## NSN 5306-00-150-9915

Clevis Bolt - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6049 spec.