## NSN 5306-00-150-9928

Clevis Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-150-9928
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.297 inches
Fastener Length:
2.906 inches
Head Style:
Button
Head Diameter:
Between 0.359 inches and 0.391 inches
Head Height:
Between 0.078 inches and 0.110 inches
Groove Diameter:
0.141 inches
Single Shear Strength:
2125 pounds per square inch
Internal Drive Style:
Slot
Thread Diameter:
0.190 inches
Thready Qty Per Inch (tpi):
32
Material:
Steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4140 or steel comp 4130 or steel comp 4037
Material Specification:
Mil-s-6049 military specification 1st material response or mil-s-6050 military specification 2nd material response or mil-s-6098 military
specification 3rd material response or mil-s-5626 military specification 4th material response or mil-s-6758 military specification 5th materia
response or mil-s-8695 military specification 6th material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2 cl 3 federal specification all treatment responses
Thread Series Designator:
Unf
Departure From Cited Document:
Thread t per mil-s-7742 except major diameter is not to exceed maximum allow bolt shank dia
Shelf Life:
N/a
Unit Of Measure:
<del></del>

No

Demilitarization:

## NSN 5306-00-150-9928

Clevis Bolt - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6049 spec.