

View Online at <https://aerobasegroup.com/nsn/5306-00-151-0160>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.681 inches

**Fastener Length:**

Between 4.328 inches and 4.375 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.265 inches and 0.297 inches

**Width Between Flats:**

Between 0.740 inches and 0.752 inches

**Shank Unthreaded Hole Diameter:**

0.106 inches first hole and 0.116 inches first hole

**Thread Diameter:**

0.500 inches

**Grip Length:**

Between 3.646 inches and 3.678 inches

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

125000 pounds per square inch

**Hardness Rating:**

26.0 rockwell c and 32.0 rockwell c

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

4.156 inches first hole and 4.188 inches first hole

**Material:**

Steel

**Surface Treatment:**

Cadmium or dichromate

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0