

View Online at <https://aerobasegroup.com/nsn/5306-00-151-0295>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.422 inches

**Fastener Length:**

3.438 inches

**Head Style:**

Button

**Head Diameter:**

Between 1.109 inches and 1.141 inches

**Head Height:**

Between 0.296 inches and 0.328 inches

**Groove Diameter:**

0.545 inches

**Shank Unthreaded Hole Diameter:**

0.141 inches first hole and 0.151 inches first hole

**Single Shear Strength:**

23000 pounds per square inch

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.625 inches

**Thready Qty Per Inch (tpi):**

18

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

3.250 inches first hole

**Material:**

Steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4140 or steel comp 4130 or steel comp 4037

**Material Specification:**

Mil-s-6049 military specification 1st material response or mil-s-6050 military specification 2nd material response or mil-s-6098 military specification 3rd material response or mil-s-5626 military specification 4th material response or mil-s-6758 military specification 5th material response or mil-s-8695 military specification 6th material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2 cl3 federal specification all treatment responses

**Thread Series Designator:**

Unf

**Departure From Cited Document:**

Hthread t per mil-s-7742 except major diameter is not to exceed maximum allow bolt shank dia

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-6049 spec.