

View Online at <https://aerobasegroup.com/nsn/5306-00-151-0671>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.360 inches

**Fastener Length:**

5.547 inches

**Head Style:**

Button

**Head Diameter:**

Between 0.859 inches and 0.891 inches

**Head Height:**

Between 0.234 inches and 0.266 inches

**Groove Diameter:**

0.422 inches

**Shank Unthreaded Hole Diameter:**

0.106 inches and 0.116 inches first hole

**Single Shear Strength:**

14700 pounds per square inch

**Internal Drive Style:**

Slot

**End Application:**

Spec item

**Thread Diameter:**

0.500 inches

**Thready Qty Per Inch (tpi):**

20

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

5.375 inches first hole

**Material:**

Steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4140 or steel comp 4130 or steel comp 4037

**Material Specification:**

Mil-s-6049 military specification 1st material response or mil-s-6050 military specification 2nd material response or mil-s-6098 military specification 3rd material response or mil-s-5626 military specification 4th material response or mil-s-6758 military specification 5th material response or mil-s-8695 military specification 6th material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416 type 2 cl 3 federal specification single treatment response

**Thread Series Designator:**

Unf

**Departure From Cited Document:**

Thread t per mil-s-7742 except major diameter is not to exceed maximum allow bolt shank dia

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-6049 spec.