

View Online at <https://aerobasegroup.com/nsn/5306-00-151-1694>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.374 inches and 0.453 inches

Fastener Length:

Between 3.641 inches and 3.688 inches

Head Style:

Hexagon

Head Height:

Between 0.109 inches and 0.141 inches

Width Between Flats:

Between 0.365 inches and 0.377 inches

Shank Unthreaded Hole Diameter:

0.070 inches and 0.080 inches first hole

End Application:

Spec item

Thread Diameter:

0.190 inches

Grip Length:

Between 3.234 inches and 3.266 inches

Features Provided:

Finished head

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

62000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

3.500 inches and 3.531 inches first hole

Material:

Aluminum alloy

Material Specification:

Qq-a-200 federal specification 1st material response or qq-a-225 federal specification 2nd material response or qq-a-430 federal specification 3rd material response

Surface Treatment:

Oxide film and anodize

Surface Treatment Specification:

Mil-c-5541 military specification 1st treatment response and mil-a-8625 military specification 2nd treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-5541 spec.