

View Online at <https://aerobasegroup.com/nsn/5306-00-151-1697>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.374 inches and 0.453 inches

**Fastener Length:**

Between 3.141 inches and 3.188 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.109 inches and 0.141 inches

**Width Between Flats:**

Between 0.365 inches and 0.377 inches

**Shank Unthreaded Hole Diameter:**

0.070 inches first hole and 0.080 inches first hole

**Thread Diameter:**

0.190 inches

**Grip Length:**

Between 2.734 inches and 2.766 inches

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

62000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

3.000 inches first hole and 3.031 inches first hole

**Material:**

Aluminum alloy

**Material Specification:**

Qq-a-200 federal specification 1st material response or qq-a-225 federal specification 2nd material response or qq-a-430 federal specification 3rd material response

**Surface Treatment:**

Oxide film and anodize

**Surface Treatment Specification:**

Mil-c-5541 military specification 1st treatment response and mil-a-8625 military specification 2nd treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-c-5541 spec.