

View Online at <https://aerobasegroup.com/nsn/5306-00-151-1781>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.782 inches

Fastener Length:

4.844 inches

Head Style:

Hexagon

Head Height:

Between 0.265 inches and 0.297 inches

Width Between Flats:

Between 0.740 inches and 0.752 inches

Hole Diameter:

0.070 inches

Grip Diameter:

Between 0.4986 inches and 0.4991 inches

Shank Unthreaded Hole Diameter:

0.106 inches first hole

Thread Diameter:

0.500 inches

Grip Length:

4.062 inches

Hole Quantity:

1

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

125000 pounds per square inch

Hardness Rating:

26.0 rockwell c and 32.0 rockwell c

Hole Configuration Style:

Hexagon flats

Distance From Head Largest Bearing Surface To Shank Hole Center:

4.671 inches first hole

Surface Finish:

63.0 microinches grip

Material:

Steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4037 or steel comp 4130 or steel comp 4140

Material Specification:

Mil-s-6049 military specification 1st material response or mil-s-6050 military specification 2nd material response or mil-s-6098 military specification 3rd material response or ams 6300 assn standard 4th material response or mil-s-6758 military specification 5th material response or mil-s-5626 military specification 6th material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, class 3 federal specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6049 spec.