

View Online at <https://aerobasegroup.com/nsn/5306-00-151-1966>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.324 inches and 0.364 inches

Fastener Length:

Between 0.896 inches and 0.916 inches

Head Style:

Button

Head Diameter:

Between 0.365 inches and 0.385 inches

Head Height:

Between 0.083 inches and 0.103 inches

Groove Diameter:

0.141 inches

Shank Unthreaded Hole Diameter:

0.070 inches first hole and 0.080 inches first hole

Single Shear Strength:

2125 pounds per square inch

Internal Drive Style:

Slot

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

125000 pounds per square inch

Hardness Rating:

26.0 rockwell c and 32.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

0.136 inches first hole and 0.146 inches first hole

Material:

Steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4140 or steel comp 4130 or steel comp 4037

Material Specification:

Mil-s-6049 military specification 1st material response or mil-s-6050 military specification 2nd material response or mil-s-6098 military specification 3rd material response or mil-s-5626 military specification 4th material response or mil-s-6758 military specification 5th material response or mil-s-8695 military specification 6th material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 type 2 cl 3 federal specification single treatment response

Thread Series Designator:

Unf

Departure From Cited Document:

Thread t per m1l-s-7742 except major d1a is not to exceed maximum allow bolt shank d1a

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6049 spec.