

View Online at <https://aerobasegroup.com/nsn/5306-00-151-1993>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.297 inches

Fastener Length:

2.297 inches

Head Style:

Button

Head Diameter:

Between 0.672 inches and 0.704 inches

Head Height:

Between 0.172 inches and 0.204 inches

Groove Diameter:

0.313 inches

Single Shear Strength:

280 pounds per square inch

Internal Drive Style:

Slot

Thread Diameter:

0.375 inches

Thready Qty Per Inch (tpi):

24

Material:

Steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4140 or steel comp 4130 or steel comp 4037

Material Specification:

Mil-s-6049 military specification 1st material response or mil-s-6050 military specification 2nd material response or mil-s-6098 military specification 3rd material response or mil-s-5626 military specification 4th material response or mil-s-6758 military specification 5th material response or mil-s-8695 military specification 6th material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Thread Series Designator:

Unf

Departure From Cited Document:

Thread t per m1l-s-4472 except major d1a is not to exceed maximum allow bolt shank d1a

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-s-6049 spec.