## NSN 5306-00-151-2652

Clevis Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-151-2652

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.276 inches
Fastener Length:
2.547 inches
Head Style:
Button
Head Diameter:
0.688 inches
Head Height:
0.188 inches
Groove Diameter:
Between 0.308 inches and 0.318 inches
Shank Unthreaded Hole Diameter:
0.106 inches first hole and 0.116 inches first hole
Single Shear Strength:
8280 pounds per square inch
Internal Drive Style:
Slot
Thread Diameter:
0.375 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
125000 pounds per square inch
Hardness Rating:
26.0 rockwell c and 32.0 rockwell c
Distance From Head Largest Bearing Surface To Shank Hole Center:
2.391 inches first hole and 2.422 inches first hole
Material:
Steel comp 4130 or steel comp 8740 or steel comp 4037
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 type 2 cl 3 federal specification single treatment response
Thread Series Designator:
Unf
Shelf Life:
N/a

## NSN 5306-00-151-2652

Clevis Bolt - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0