

View Online at <https://aerobasegroup.com/nsn/5306-00-151-3129>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.906 inches

**Fastener Length:**

3.156 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.296 inches and 0.328 inches

**Width Between Flats:**

Between 0.865 inches and 0.877 inches

**Shank Unthreaded Hole Diameter:**

0.141 inches first hole

**Thread Diameter:**

0.562 inches

**Grip Length:**

2.250 inches

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

18

**Min. Tensile Strength (psi):**

125000 pounds per square inch

**Hardness Rating:**

26.0 rockwell c and 32.0 rockwell c

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

2.906 inches first hole

**Material:**

Steel comp 4037 or steel comp 4130 or steel comp 8630 or steel comp 8735 or steel comp 8740 or steel comp 4140

**Material Specification:**

Mil-b-6812 military specification all material responses

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, class 3 federal specification all treatment responses

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-b-6812 spec.