

View Online at <https://aerobasegroup.com/nsn/5306-00-151-3276>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.640 inches

Fastener Length:

2.828 inches

Head Style:

Hexagon

Head Height:

Between 0.203 inches and 0.235 inches

Width Between Flats:

Between 0.553 inches and 0.565 inches

Shank Unthreaded Hole Diameter:

0.106 inches first hole

Thread Diameter:

0.375 inches

Grip Length:

2.188 inches

Features Provided:

Finished head

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

62000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

2.626 inches first hole

Material:

Aluminum alloy 2024 or aluminum alloy 1100 or aluminum alloy 2017 or aluminum alloy 2117 or aluminum alloy 5056

Material Specification:

Qq-a-267 federal specification 1st material response or qq-a-268 federal specification 1st material response or mil-w-7986 military specification 1st material response or mil-w-7986 military specification 2nd material response or mil-w-7986 military specification 3rd material response or mil-w-7986 military specification 4th material response or mil-w-7986 military specification 5th material response

Surface Treatment:

Oxide film and anodize

Surface Treatment Specification:

Mil-c-5541 military specification 1st treatment response and mil-a-8625 military specification 2nd treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-w-7986 spec.