

View Online at <https://aerobasegroup.com/nsn/5306-00-151-5755>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.680 inches

Fastener Length:

1.880 inches

Head Style:

Hexagon

Head Height:

0.300 inches

Width Between Flats:

Between 0.616 inches and 0.627 inches

Shank Unthreaded Hole Diameter:

0.093 inches first hole and 0.099 inches first hole

First Diameter From Head:

Between 0.400 inches and 0.410 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 1.100 inches and 1.150 inches

Thread Diameter:

0.438 inches

Thready Qty Per Inch (tpi):

20

Hardness Rating:

35.0 rockwell c and 40.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.680 inches first hole

Externally Relieved Body Diameter Quantity:

1

Material:

Steel

Material Specification:

Mil-s-6049 per ams 6322 military specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 1, cl b per hs 74 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6049 spec.