## NSN 5306-00-151-5775

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-151-5775

| Thread Class:  |
|--|
| 3a   |
| Thread Direction:  |
| Right-hand   |
| Thread Length:   |
| Between 1.660 inches and 1.680 inches  |
| Fastener Length:   |
| 3.670 inches   |
| Head Style:  |
| Double hexagon w/hole  |
| Head Height:   |
| 1.051 inches   |
| Width Between Flats:   |
| Between 1.239 inches and 1.252 inches  |
| Extended Washer Diameter:  |
| Between 1.865 inches and 1.875 inches  |
| Extended Washer Thickness:   |
| 0.258 inches   |
| Grip Diameter:   |
| Between 1.1225 inches and 1.1240 inches  |
| Thread Diameter:   |
| 1.125 inches   |
| Grip Length:   |
| Between 1.1990 inches and 2.010 inches   |
| Thready Qty Per Inch (tpi):  |
| 12   |
| Min. Tensile Strength (psi):   |
| 180000 pounds per square inch  |
| Hardness Rating:   |
| 39.0 rockwell c and 43.0 rockwell c  |
| Material:  |
| Steel comp 8740 or steel comp 4340 or steel comp e4340 or steel comp 6150 or steel comp 4140 |
| Surface Treatment:   |
| Cadmium and chromate   |
| Surface Treatment Specification:   |
| Qq-p-416, type 2, cl 2 federal specification all treatment responses                         |
| Thread Series Designator:  |
| Unjf   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |

--

## NSN 5306-00-151-5775

Shear Bolt - Page 2 of 2



| Demi |  |  |  |
|------|--|--|--|
|      |  |  |  |
|      |  |  |  |

No

Fiig:

A003b0