

View Online at <https://aerobasegroup.com/nsn/5306-00-151-6179>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.325 inches and 0.392 inches

**Fastener Length:**

Between 1.460 inches and 1.507 inches

**Head Style:**

Double hexagon

**Head Height:**

0.187 inches

**Width Between Flats:**

Between 0.492 inches and 0.502 inches

**Grip Diameter:**

Between 0.3110 inches and 0.3120 inches

**Shank Unthreaded Hole Diameter:**

0.076 inches first hole and 0.086 inches first hole

**Thread Diameter:**

0.312 inches

**Grip Length:**

Between 0.115 inches and 0.135 inches

**Thready Qty Per Inch (tpi):**

24

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.341 inches first hole and 1.373 inches first hole

**Surface Finish:**

32.0 microinches grip

**Material:**

Steel

**Material Specification:**

H-11, sts bs000, fscm 98897 mfr ref single material response

**Surface Treatment:**

Nickel and cadmium and chromate

**Surface Treatment Specification:**

Sts bs 000, lockheed-georgia co mfr ref all treatment responses

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0