

View Online at <https://aerobasegroup.com/nsn/5306-00-151-6257>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.475 inches and 0.542 inches

Fastener Length:

Between 1.423 inches and 1.470 inches

Head Style:

Hexagon

Head Height:

Between 0.140 inches and 0.172 inches

Width Between Flats:

Between 0.490 inches and 0.502 inches

Grip Diameter:

Between 0.3115 inches and 0.3120 inches

Thread Diameter:

0.312 inches

Grip Length:

Between 0.928 inches and 0.948 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

185000 pounds per square inch

Hardness Rating:

40.0 rockwell c and 46.0 rockwell c

Product Name:

Navy special project

Material:

Stainless steel

Material Specification:

Nas1597 cond f, fscm 80205 mfr ref single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-s-5002 military specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas1588 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5002 spec.