

View Online at <https://aerobasegroup.com/nsn/5306-00-151-6870>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.499 inches and 0.578 inches

**Eye Inside Diameter:**

Between 0.250 inches and 0.253 inches

**Shoulder Thickness:**

Between 0.078 inches and 0.110 inches

**Shank Length:**

Between 0.703 inches and 0.735 inches

**Eye Stock Thickness:**

Between 0.172 inches and 0.204 inches

**Shoulder Diameter:**

Between 0.609 inches and 0.641 inches

**Overall Length:**

Between 1.593 inches and 1.625 inches

**Thread Diameter:**

0.312 inches

**Thready Qty Per Inch (tpi):**

24

**Distance From Center Of Eye To Shank End:**

Between 0.952 inches and 1.016 inches

**Eye Outside Width:**

Between 0.609 inches and 0.641 inches

**Special Features:**

Eye countersink 0.030 in. By 45 degrees both sides

**Material:**

Steel comp 4140 or steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4130 or steel

**Material Specification:**

Mil-s-5626 military specification 1st material response or mil-s-6049 military specification 2nd material response or mil-s-6050 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6758 military specification 5th material response or sae assn standard 6th material response or ams 6300 assn standard 7th material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, class 3 federal specification single treatment response

**Style Designator:**

Round, closed w/shoulder

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5626 spec.