

View Online at <https://aerobasegroup.com/nsn/5306-00-151-6914>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.505 inches and 0.535 inches

Fastener Length:

Between 0.916 inches and 0.936 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.328 inches and 0.348 inches

Width Between Flats:

0.3750 inches

Extended Washer Diameter:

Between 0.490 inches and 0.510 inches

Extended Washer Thickness:

Between 0.070 inches and 0.080 inches

Shoulder Diameter:

0.3115 inches first shoulder and 0.3120 inches first shoulder

Shoulder Length:

0.401 inches first shoulder and 0.411 inches first shoulder

Hole Diameter:

0.100 inches

Thread Diameter:

0.250 inches

Hole Quantity:

4

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

28

Hole Configuration Style:

Double hexagon longitudinal hole

Criticality Code Justification:

Aatn

Shoulder Shape:

Round first shoulder

Material:

Iron alloy 660

Material Specification:

Ams 5731 assn standard single material response

Precious Material:

Silver

Surface Treatment:

Silver threads

Surface Treatment Specification:

Ams 2410 assn standard single treatment response threads

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0