## NSN 5306-00-151-6914

Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-151-6914 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.505 inches and 0.535 inches **Fastener Length:** Between 0.916 inches and 0.936 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.328 inches and 0.348 inches Width Between Flats: 0.3750 inches **Extended Washer Diameter:** Between 0.490 inches and 0.510 inches **Extended Washer Thickness:** Between 0.070 inches and 0.080 inches **Shoulder Diameter:** 0.3115 inches first shoulder and 0.3120 inches first shoulder **Shoulder Length:** 0.401 inches first shoulder and 0.411 inches first shoulder **Hole Diameter:** 0.100 inches **Thread Diameter:** 0.250 inches **Hole Quantity:** Hole Type: Drilled Thready Qty Per Inch (tpi): **Hole Configuration Style:** Double hexagon longitudinal hole **Criticality Code Justification:** Aatn **Shoulder Shape:** Round first shoulder

Material:

Iron alloy 660

**Material Specification:** 

Ams 5731 assn standard single material response

## **NSN 5306-00-151-6914** Shoulder Bolt - Page 2 of 2

A003b0



Precious Material:
Silver
Surface Treatment:
Silver threads
Surface Treatment Specification:
Ams 2410 assn standard single treatment response threads
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
<del>.</del>
Demilitarization:
No
Fiia: