

View Online at <https://aerobasegroup.com/nsn/5306-00-151-6955>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.750 inches and 0.810 inches

Fastener Length:

4.625 inches

Head Style:

Double hexagon w/hole

Head Height:

0.300 inches

Width Between Flats:

0.313 inches

Extended Washer Diameter:

0.438 inches

Extended Washer Thickness:

Between 0.060 inches and 0.070 inches

First Diameter From Head:

Between 0.190 inches and 0.195 inches

Second Diameter From Head:

Between 0.248 inches and 0.249 inches

Third Diameter From Head:

Between 0.190 inches and 0.195 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

2.280 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

2.530 inches

Distance From Largest Bearing Surface Of Head To End Of Third Diameter:

Between 3.815 inches and 3.875 inches

Thread Diameter:

0.250 inches

Thready Qty Per Inch (tpi):

28

Externally Relieved Body Diameter Quantity:

3

Material:

Iron alloy 660

Material Specification:

Ams 5731 assn standard single material response

Test Data Document:

81343-ams2645 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0