

View Online at <https://aerobasegroup.com/nsn/5306-00-151-6955>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.750 inches and 0.810 inches

**Fastener Length:**

4.625 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

0.300 inches

**Width Between Flats:**

0.313 inches

**Extended Washer Diameter:**

0.438 inches

**Extended Washer Thickness:**

Between 0.060 inches and 0.070 inches

**First Diameter From Head:**

Between 0.190 inches and 0.195 inches

**Second Diameter From Head:**

Between 0.248 inches and 0.249 inches

**Third Diameter From Head:**

Between 0.190 inches and 0.195 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

2.280 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

2.530 inches

**Distance From Largest Bearing Surface Of Head To End Of Third Diameter:**

Between 3.815 inches and 3.875 inches

**Thread Diameter:**

0.250 inches

**Thready Qty Per Inch (tpi):**

28

**Externally Relieved Body Diameter Quantity:**

3

**Material:**

Iron alloy 660

**Material Specification:**

Ams 5731 assn standard single material response

**Test Data Document:**

81343-ams2645 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0