
# NSN 5306-00-151-9545

Shear Bolt - Page 1 of 2





# **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Thread Length:

Between 0.298 inches and 0.348 inches

# Fastener Length:

Between 0.620 inches and 0.650 inches

### **Head Style:**

Dished hexagon

### **Head Height:**

Between 0.110 inches and 0.125 inches

### Width Between Flats:

Between 0.367 inches and 0.376 inches

#### **Grip Diameter:**

Between 0.1890 inches and 0.1895 inches

### **Thread Diameter:**

0.190 inches

# Grip Length:

Between 0.302 inches and 0.322 inches

# Thready Qty Per Inch (tpi):

32

# Min. Tensile Strength (psi):

160000 pounds per square inch

# Surface Finish:

32.0 microinches threads

### Material:

Iron alloy 660

### **Material Specification:**

Ams 5731 assn standard single material response or ams 5737 assn standard single material response

#### Surface Treatment:

Passivate

### **Thread Series Designator:**

Unjf

### **Specification Data:**

80205-nas6303 professional/industrial association standard

#### Shelf Life:

N/a

# Unit Of Measure:

--

# Demilitarization:

No

# NSN 5306-00-151-9545

Shear Bolt - Page 2 of 2

Fiig: A003b0

