

View Online at <https://aerobasegroup.com/nsn/5306-00-152-2642>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.438 inches

**Fastener Length:**

1.219 inches

**Head Style:**

Hexagon

**Head Height:**

0.234 inches

**Width Between Flats:**

0.562 inches

**Hole Diameter:**

0.078 inches

**Shank Unthreaded Hole Diameter:**

0.078 inches first hole

**First Diameter From Head:**

0.320 inches

**Second Diameter From Head:**

0.375 inches

**Third Diameter From Head:**

0.320 inches

**Fourth Diameter From Head:**

0.375 inches

**Fifth Diameter From Head:**

0.320 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

0.125 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

0.313 inches

**Distance From Largest Bearing Surface Of Head To End Of Third Diameter:**

0.438 inches

**Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:**

0.626 inches

**Distance From Largest Bearing Surface Of Head To End Of Fifth Diameter:**

0.781 inches

**Thread Diameter:**

0.375 inches

**Hole Quantity:**

6

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

24

**Hole Configuration Style:**

Hexagon flats

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.109 inches first hole

**Externally Relieved Body Diameter Quantity:**

5

**Material:**

Steel comp 6150

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0