

View Online at <https://aerobasegroup.com/nsn/5306-00-152-2642>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.438 inches

Fastener Length:

1.219 inches

Head Style:

Hexagon

Head Height:

0.234 inches

Width Between Flats:

0.562 inches

Hole Diameter:

0.078 inches

Shank Unthreaded Hole Diameter:

0.078 inches first hole

First Diameter From Head:

0.320 inches

Second Diameter From Head:

0.375 inches

Third Diameter From Head:

0.320 inches

Fourth Diameter From Head:

0.375 inches

Fifth Diameter From Head:

0.320 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

0.125 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

0.313 inches

Distance From Largest Bearing Surface Of Head To End Of Third Diameter:

0.438 inches

Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:

0.626 inches

Distance From Largest Bearing Surface Of Head To End Of Fifth Diameter:

0.781 inches

Thread Diameter:

0.375 inches

Hole Quantity:

6

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

24

Hole Configuration Style:

Hexagon flats

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.109 inches first hole

Externally Relieved Body Diameter Quantity:

5

Material:

Steel comp 6150

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0