

View Online at <https://aerobasegroup.com/nsn/5306-00-152-5193>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

1.500 inches

Fastener Length:

4.139 inches

Head Style:

Round w/wrench flats

Head Diameter:

1.875 inches

Head Height:

1.062 inches

Width Between Flats:

1.625 inches

Hole Diameter:

0.141 inches

Shank Unthreaded Hole Diameter:

0.140 inches first hole

Concentric Hole Depth:

4.312 inches

Counterbore Diameter:

0.625 inches

Counterbore Depth:

1.125 inches

Concentric Hole Diameter:

0.484 inches

Thread Diameter:

1.125 inches

Hole Quantity:

2

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

12

Min. Tensile Strength (psi):

150000 pounds per square inch

Hardness Rating:

33.0 rockwell c and 37.0 rockwell c

Hole Configuration Style:

Round

Distance From Head Largest Bearing Surface To Shank Hole Center:

3.826 inches first hole

Material:

Steel comp e4340

Material Specification:

Mil-s-5000 military specification single material response

Surface Treatment:

Cadmium

Style Designator:

Counterbore unthreaded

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.