

View Online at <https://aerobasegroup.com/nsn/5306-00-152-5303>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 1.127 inches and 1.177 inches

**Fastener Length:**

Between 3.199 inches and 3.229 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

0.673 inches

**Width Between Flats:**

Between 0.803 inches and 0.814 inches

**Extended Washer Diameter:**

Between 1.185 inches and 1.195 inches

**Extended Washer Thickness:**

0.125 inches

**Grip Diameter:**

Between 0.6230 inches and 0.6240 inches

**Thread Diameter:**

0.625 inches

**Grip Length:**

Between 2.052 inches and 2.062 inches

**Thready Qty Per Inch (tpi):**

18

**Min. Tensile Strength (psi):**

260000 pounds per square inch

**Hardness Rating:**

51.0 rockwell c and 54.0 rockwell c

**Material:**

Vanadium

**Material Specification:**

Vasc0 jetm-a, fscm 87665 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Mil-c-8837 type 2, cl 3 military specification single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

56878-ewb26 manufacturers standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-c-8837 spec.