

View Online at <https://aerobasegroup.com/nsn/5306-00-156-2224>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.750 inches and 0.828 inches

**Fastener Length:**

Between 1.953 inches and 2.000 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.265 inches and 0.297 inches

**Width Between Flats:**

Between 0.740 inches and 0.752 inches

**Shank Unthreaded Hole Diameter:**

0.106 inches first hole and 0.116 inches first hole

**Thread Diameter:**

0.500 inches

**Grip Length:**

Between 1.172 inches and 1.203 inches

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

62000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.781 inches first hole and 1.828 inches first hole

**Material:**

Aluminum alloy

**Material Specification:**

Qq-a-200 federal specification single material response or qq-a-225 federal specification single material response or qq-a-430 federal specification single material response

**Surface Treatment:**

Oxide film and anodize

**Surface Treatment Specification:**

Mil-c-5541 military specification 1st treatment response and mil-a-8625 military specification 2nd treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-c-5541 spec.