

View Online at <https://aerobasegroup.com/nsn/5306-00-156-2279>

**Thread Class:**

3a

**Thread Length:**

Between 0.438 inches and 0.516 inches

**Fastener Length:**

Between 2.266 inches and 2.297 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.140 inches and 0.172 inches

**Width Between Flats:**

Between 0.428 inches and 0.440 inches

**Shank Unthreaded Hole Diameter:**

0.076 inches first hole and 0.086 inches first hole

**Thread Diameter:**

0.250 inches

**Grip Length:**

Between 1.797 inches and 1.828 inches

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

125000 pounds per square inch

**Hardness Rating:**

26.0 rockwell c and 32.0 rockwell c

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

2.109 inches first hole and 2.141 inches first hole

**Material:**

Steel comp 431

**Material Specification:**

Mil-s-18732 military specification single material response

**Surface Treatment:**

Passivate

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-s-18732 spec.