# NSN 5306-00-156-2293

Clevis Bolt - Page 1 of 2



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

#### Thread Length:

Between 0.323 inches and 0.363 inches

#### Fastener Length:

Between 2.646 inches and 2.666 inches

#### Head Style:

Button

Head Diameter:

Between 0.484 inches and 0.500 inches

#### **Head Height:**

Between 0.109 inches and 0.141 inches

#### Groove Diameter:

Between 0.191 inches and 0.201 inches

#### Single Shear Strength:

3680 pounds per square inch

#### Internal Drive Style:

Slot

#### Thread Diameter:

0.250 inches

#### Thready Qty Per Inch (tpi):

28

#### Material:

Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740

# Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military

specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th material response

#### Surface Treatment:

Cadmium and chromate

# Surface Treatment Specification:

Qq-p-416 type 2 cl 3 federal specification single treatment response

# Thread Series Designator:

Unf

Shelf Life:

N/a

### Unit Of Measure:

--

#### Demilitarization:

No

Fiig:

A003b0



# NSN 5306-00-156-2293

Clevis Bolt - Page 2 of 2

# Mil-std (military Standard):

Mil-s-5626 spec.

