## NSN 5306-00-156-2293



Clevis Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-00-156-2293 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.323 inches and 0.363 inches **Fastener Length:** Between 2.646 inches and 2.666 inches **Head Style: Button Head Diameter:** Between 0.484 inches and 0.500 inches **Head Height:** Between 0.109 inches and 0.141 inches **Groove Diameter:** Between 0.191 inches and 0.201 inches Single Shear Strength: 3680 pounds per square inch **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Material: Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740 **Material Specification:** Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2 cl 3 federal specification single treatment response **Thread Series Designator:** Unf

Qq-p-416 type 2 cl 3 federal specification single treatment response
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
-Demilitarization:
No
Fiig:

A003b0

## NSN 5306-00-156-2293

Clevis Bolt - Page 2 of 2



Mil-std (military Standard):

Mil-s-5626 spec.