## NSN 5306-00-159-2764

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-159-2764 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.565 inches and 0.615 inches **Fastener Length:** Between 1.575 inches and 1.605 inches **Head Style:** Double hexagon w/hole **Head Height:** 0.348 inches Width Between Flats: Between 0.367 inches and 0.376 inches **Extended Washer Diameter:** Between 0.521 inches and 0.531 inches **Extended Washer Thickness:** Between 0.072 inches and 0.092 inches **Grip Diameter:** Between 0.3110 inches and 0.3120 inches **Thread Diameter:** 0.312 inches **Grip Length:** Between 0.990 inches and 1.010 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 220000 pounds per square inch Material: Steel **Material Specification:** H-11 stsbs002, fscm 98897 mfr ref single material response **Surface Treatment:** Nickel and cadmium and chromate **Surface Treatment Specification:** Stsbs 002, lockheed-georgia co mfr ref all treatment responses **Thread Series Designator:** Unjf Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5306-00-159-2764

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0