## NSN 5306-00-159-2765

Shear Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-00-159-2765



**Thread Class:** 

3a

**Thread Direction:** 

**Right-hand** 

Thread Length:

Between 0.790 inches and 0.840 inches

Fastener Length:

Between 3.925 inches and 3.955 inches

**Head Style:** 

Double hexagon w/hole

**Head Height:** 

0.504 inches

Width Between Flats:

Between 0.553 inches and 0.564 inches

#### **Extended Washer Diameter:**

Between 0.818 inches and 0.828 inches

#### **Extended Washer Thickness:**

Between 0.113 inches and 0.133 inches

#### **Grip Diameter:**

Between 0.4985 inches and 0.4995 inches

## Thread Diameter:

0.500 inches

Grip Length:

Between 3.115 inches and 3.135 inches

## Thready Qty Per Inch (tpi):

20

## Min. Tensile Strength (psi):

220000 pounds per square inch

#### Material:

Steel

## **Material Specification:**

H-11 stsbs002, fscm 98897 mfr ref single material response

#### Surface Treatment:

Nickel and cadmium and chromate

## Surface Treatment Specification:

Stsbs 002, lockheed-georgia co mfr ref all treatment responses

## **Thread Series Designator:**

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

# NSN 5306-00-159-2765

Shear Bolt - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

