NSN 5306-00-163-6634

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-163-6634 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.740 inches and 0.820 inches **Fastener Length:** Between 1.178 inches and 1.198 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.330 inches and 0.340 inches Width Between Flats: Between 0.304 inches and 0.313 inches **Extended Washer Diameter:** Between 0.428 inches and 0.448 inches **Extended Washer Thickness:** Between 0.060 inches and 0.070 inches **Hole Diameter:** 0.330 inches **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.378 inches and 0.438 inches **Hole Quantity:** 2 **Hole Type:** Drilled **Features Provided:** Finished head Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 125000 pounds per square inch **Hardness Rating:** 26.0 rockwell c and 32.0 rockwell c **Hole Configuration Style:** Double hexagon flats

Double hexagon flats

Surface Finish:
63.0 microinches grip

Product Name:
Navy special project

NSN 5306-00-163-6634 Machine Bolt - Page 2 of 2



| Material: |
|---|
| Steel comp 8740 |
| Material Specification: |
| Ams 6322 assn standard single material response |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A003b0