

View Online at <https://aerobasegroup.com/nsn/5306-00-163-9359>

Thread Class:

3a

Thread Length:

Between 0.645 inches and 0.675 inches

Fastener Length:

Between 7.940 inches and 7.960 inches

Head Style:

Hexagon

Head Height:

Between 0.240 inches and 0.260 inches

Width Between Flats:

Between 0.679 inches and 0.690 inches

Shank Unthreaded Hole Diameter:

0.094 inches first hole and 0.101 inches first hole

First Diameter From Head:

Between 0.5100 inches and 0.5105 inches

Second Diameter From Head:

Between 0.290 inches and 0.310 inches

Third Diameter From Head:

Between 0.5100 inches and 0.5105 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 2.080 inches and 2.100 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

Between 5.185 inches and 5.215 inches

Distance From Largest Bearing Surface Of Head To End Of Third Diameter:

Between 7.285 inches and 7.295 inches

Distance From Head Largest Bearing Surface To Shank Hole Center:

7.710 inches first hole and 7.720 inches first hole

Material:

Nickel alloy 718

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0