## NSN 5306-00-164-4252

Internally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-164-4252 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.330 inches and 0.350 inches **Fastener Length:** Between 1.920 inches and 1.930 inches **Head Style:** Round w/wrench flats **Head Diameter:** 1.300 inches **Head Height:** Between 0.150 inches and 0.160 inches Width Between Flats: 1.125 inches **Concentric Hole Depth:** 1.950 inches **Concentric Hole Diameter:** Between 0.401 inches and 0.411 inches **Thread Diameter:** 0.781 inches Thready Qty Per Inch (tpi): 32 **Special Features:** Seven holes equally spaced0.077 in. Min dia, 0.080 in. Maximum dia, 1.754 in. From bearingsurface of head Material: Steel comp 4340 **Surface Treatment:** Oxide **Surface Treatment Specification:** Mil-c-13924, cl 1 military specification single treatment response **Style Designator:** Concentric hole unthreaded **Test Data Document:** 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Thread Series Designator:** Uns

N/a

Shelf Life:

**Unit Of Measure:** 

## NSN 5306-00-164-4252

Internally Relieved Body Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.