
Internally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-164-4252

Thread Cla	ss:
За	
Thread Dir	ection:
Right-hand	
Thread Ler	igth:
Between 0.	330 inches and 0.350 inches
Fastener L	ength:
Between 1.	020 inches and 1.930 inches
Head Style	
Round w/w	ench flats
Head Diam	eter:
1.300 inche	S
Head Heigl	nt:
Between 0.	150 inches and 0.160 inches
Width Betv	veen Flats:
1.125 inche	S
Concentric	Hole Depth:
1.950 inche	S
Concentric	Hole Diameter:
Between 0.	101 inches and 0.411 inches
Thread Dia	meter:
0.781 inche	S
Thready Q	y Per Inch (tpi):
32	
Special Fea	atures:
Seven hole	s equally spaced0.077 in. Min dia, 0.080 in. Maximum dia, 1.754 in. From bearingsurface of head
Material:	
Steel comp	4340
Surface Tr	eatment:
Oxide	
Surface Tr	eatment Specification:
Mil-c-13924	, cl 1 military specification single treatment response
Style Desig	inator:
Concentric	nole unthreaded
Test Data I	Document:
81349-mil-i-	6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; exc	ludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmen	tal and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Ser	ies Designator:
Uns	
Shelf Life:	
N/a	
Unit Of Me	asure:

NSN 5306-00-164-4252

Internally Relieved Body Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.